

Zerust® OPS Preservation Tape

Use Zerust®/Excor® Preservation Tape for sealing and reinforcing seams on preservation film. Zerust preservation tape combined with VCI outdoor preservation film provides superior corrosion and UVI protection for up to two years outdoors.

Zerust/Excor Preservation Tape is designed to be used with Zerust/Excor OPS Outdoor Preservation Shrink Film to provide advanced protection to metals. It is designed to bond to Zerust VCI films, with UV stabilizers for 2-year outdoor protection.

This specially designed Zerust preservation tape is ideal for sealing and reinforcing seams, heat sealed or not. Zerust Preservation Tape will form a bond with the film. This self-wound tape exhibits good shear properties under moderate loads, has a wide service temperature range, and excellent UV resistance. Check with your Zerust/Excor representative for a corrosion management solution most effective for your metal assets.

Application Example

Valuable assets are protected from corrosion when stored outdoors. Zerust film and tape enables items to be stored near the project site and be operationally ready.



Benefits

- High-strength and performance
- Wide service temperature range
- Proven UV protection
- Excellent adhesive properties
- Maintains a watertight seal in harsh weather conditions

Application Type

- Mothballing
- Outdoor Storage
- Overseas Shipping

Specifications



Product Information Zerust®/Excor® OPS Permanent Tape is a heat responsive durable tape that shrinks, bonds to PE film and forms a durable package.

Appearance Stock colors are opaque dark gray or white.

Protected Metal Types Non-VCI Product

Service Life Outdoor UV protection for up to 2 years

Storage Store in original packaging away from direct sunlight in conditions between 60°F-80°F (15°C-27°C) and 50% RH for up to 3 years from the date of shipment.

Technical Data

Product	Gray Preservation Tape Part #: 250-X-00002	Gray Preservation Tape Part #: 250-X-00003	White Preservation Tape Part #: 250-X-00001
Product Width	4" (102 mm)	6" (144 mm)	144 mm (6")
Product Length	180' (55 m)	180' (55 m)	55 m (180')
Total Thickness	6 mil (152 µm)	6 mil (152 µm)	7 mil (178 µm)
Adhesive Thickness	2 mil (51 µm)	2 mil (51 µm)	3.5 mil (89 µm)
Carrier	Polyethylene	Polyethylene	Polyethylene
Adhesive	Acrylic	Acrylic	Synthetic Rubber
Adhesion	89 oz/in (6 kg/cm)	89 oz/in (6 kg/cm)	60 oz/in (4 kg/cm)
Service Temperature Range	-20°F to 160°F (-7°C to 71°C)	-20°F to 160°F (-7°C to 71°C)	-20°F to 160°F (-7°C to 71°C)
Optimal Usage Temperature	40°F to 160°F (4°C to 71°C)	40°F to 160°F (4°C to 71°C)	40°F to 120°F (4°C to 71°C)
Service Life	2 years	2 years	1 year

Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2019 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor. Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastab®, Z-CIS®, Zerion®, ZERUST®, 洁乐特 and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Contact Us



A product of:
Northern Technologies
International Corp
4201 Woodland Road,
Circle Pines, MN 55014
USA

Availability

Stock Offerings:

Zerust/Excor OPS Preservation Tape is sold in cases (Number of rolls per case listed below).

Gray Preservation Tape
Part Number: 250-X-00002
4" x 180' x 6 mil (12 rolls/case)

Gray Preservation Tape
Part Number: 250-X-00003
6" x 180' x 6 mil (12 rolls/case)

White Preservation Tape
Part Number: 250-X-00001
144 mm x 55 m x 7 mil (8 rolls/case)

Recyclable

Dispose of in accordance with local, national and international regulations. Check on options for recycling and incineration.

Safety

- Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHMIS regulations.
- Zerust VCI chemistry is safe for sensitive electronics. No galvanic effects, residues or changes in the properties of metals. The protective molecules dissipate upon opening of package.

Phone. +1 763.225.6600
Fax. +1 763.225.6645
sales@zerust.com
www.zerust.com

