

Prevent flash-corrosion on freshly worked metal surfaces with Zerust®/Excor® ICT® ActivTab™(LS). The tablets can be dropped into spaces and contain proven Zerust ICT corrosion inhibitors. The tablets work fast to protect ferrous and aluminum metals against flash-corrosion.

Zerust ICT ActivTabs provide superior corrosion protection for metal items in small or hard-to-reach areas such as electronic enclosures, inside of pipes, or internal areas of large containers. Simply place or sprinkle Zerust ActivTabs in the desired area and tightly seal closed. The ActivTab rapidly diffuses its protective vapor to keep ferrous metal items free of corrosion.

The tablets work fast to protect ferrous metals and aluminum against flash-corrosion and continue to protect for up to six months in an enclosure. When used as instructed, ActivTab also protects yellow metals such as copper and brass. Do not place in direct contact with copper, brass or zinc and test before use.

# **•**

#### **Benefits**

Safe\* and effective Zerust corrosion protection

Easy to install, economical to use

Fast-acting protection against flash corrosion

Works to protect in hard-to-reach and restricted spaces

Nitrite-free\*\* formula

## **Application Example**

Zerust ActivTabs are small, easy-to-use, targeted corrosion protection for hard-to-reach areas of packages or equipment in corrosive environments.



## **Application Type**

Storage
Shipping
During Operation
May be used with Zerust Packaging

- \*Safe to use and handle. Product is not hazardous for people or the environment according to EU (CLP) or OSHA HazCom 2012 (US GHS).
- \*\*Manufactured on equipment shared with products containing sodium nitrite.







Zerust® ActivTab™ Tablets are fast-acting, effective drop-in protection

## **Specifications**

Product Information	Zerust®/Excor® ActivTab™ Capsules are VCI (Vapor Corrosion Inhibitor) diffusers.		
Protected Metal Types	Ferrous and aluminum protection. Limited yellow metal protection when used as instructed. Do not place in direct contact with copper, brass or zinc and test before use.		
Storage	Store in a cool, dry place and away from sunlight in original packaging for up to 2 years from the date of shipment.		



### **Availability**

Zerust/Excor ActivTab Bottles are sold in cases of 8 bottles.

AT-25	Units/Bottle		
450-M-00100	600 tablets		

## **Protection Capabilities\***

Zerust <sup>®</sup> Product Name	Normal Environment**		Aggressive Environment**	
	Volume of Protection	Duration of Protection (Up To)	Volume of Protection	Duration of Protection (Up To)
ActivTab™(LS)-25	0.25 ft <sup>3</sup> (0.0071 m <sup>3</sup> )	6 months	0.025 ft <sup>3</sup> (0.0007 m <sup>3</sup> )	15 days
ActivCapsule <sup>™</sup> FAC1-1s	4 ft <sup>3</sup> (0.12 m <sup>3</sup> )	1 year	0.35 ft <sup>3</sup> (0.01 m <sup>3</sup> )	1 month
ActivPak®(LS)-T330	5 ft <sup>3</sup> (0.15 m <sup>3</sup> )	1 year	2 ft <sup>3</sup> (0.05 m <sup>3</sup> )	2 months
ActivPak(LS)-33	16 ft³ (0.45 m³)	1 year	5 ft <sup>3</sup> (0.15 m <sup>3</sup> )	2 months
ActivPak(LS)-T350	26 ft <sup>3</sup> (0.75 m <sup>3</sup> )	1 year	7 ft <sup>3</sup> (0.2 m <sup>3</sup> )	2 months
ActivPak(LS)-35	35 ft³ (1 m³)	1 year	11 ft³ (0.3 m³)	2 months
ActivPak-T330	5 ft <sup>3</sup> (0.15 m <sup>3</sup> )	2 years	2 ft <sup>3</sup> (0.05 m <sup>3</sup> )	4 months
ActivPak-33	16 ft³ (0.45 m³)	2 years	5 ft <sup>3</sup> (0.15 m <sup>3</sup> )	4 months
ActivPak-T350	26 ft³ (0.75 m³)	2 years	7 ft³ (0.2 m³)	4 months
ActivPak-35	35 ft³ (1 m³)	2 years	11 ft³ (0.3 m³)	4 months

\* Protection ratings are based on the highest average tested protection properties and are not guaranteed. Results may vary

Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, www.zerust.com/warranty.

©2013-2019 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastab®, Z-CIS®, Zerion®, ZERUST®, 洁乐特 and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

#### **Precautions**

- Test before use if there is a high amount of copper, brass or zinc surfaces near the capsule in the enclosure.
- Manufactured on equipment shared with products containing sodium nitrite.

#### **Contact Us**



A product of: Northern Technologies International Corp 4201 Woodland Road Circle Pines, MN 55014 **USA** 

Phone. +1 763.225.6600 Fax. +1 763.225.6645 sales@zerust.com www.zerust.com



<sup>\*\*</sup> Normal environment (below 0.2 ppm SO<sub>2</sub>) defined as warehouses, light industrial areas, and shipping and storage in sealed packaging or enclosures. Aggressive environment (at or above 0.2 ppm SO<sub>2</sub>) defined as areas located in the vicinity of salts and acid gases such as oceans, petrochemical sites, wastewater treatment and pulp-paper plants or in enclosures that are not well sealed.